



## Technical Data Sheet

### PRODUCT OVERVIEW

TEXICRYL® 13-319 is a hydrophobically modified alkali swellable emulsion designed for use as a rheology modifier in waterbased formulations. It is highly effective in modifying viscosities at low shear rates to avoid both settling and sagging.

#### CHARACTERISTICS

(Not to be taken as a specification)

Solids content	30%
Viscosity at 25°C (Brookfield RVT, Spindle 2, 100 rpm)	25 mPa s
pH	3.0
Specific gravity at 25°C	1.05
Particle size	110 nm

### APPLICATION

TEXICRYL 13-319 has been designed for use in the formulation of textured coatings, woodstains, paints and waterborne coating systems.

### PACKAGING AND STORAGE

TEXICRYL 13-319 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-319 should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Protect from frost and extended exposure to direct sunlight.

### HEALTH AND SAFETY

Please see separate material safety data sheet.

[www.scottbader.com](http://www.scottbader.com)

#### Scott Bader UK Office

Wollaston  
Wellingborough  
Northants  
NN29 7RL  
UK

Tel: +44 (0)1933 666738

email: [enquiries@scottbader.com](mailto:enquiries@scottbader.com)