



Technical Data Sheet

PRODUCT OVERVIEW

TEXICRYL® 13-687 is a high performance water-based Adhesion Promoted Pure Acrylic emulsion which has been specifically developed for use in high performance coatings for interior and exterior applications. This polymer is in line with "Green Technology" in that it is APEO free, <0.1% VOC and a low odour emulsion.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	48%
Viscosity at 25°C (Brookfield RVT RV8 Spindle 4 rpm 100)	255 mPas
pH	8.0
Specific gravity at 25°C	1.04
Minimum film formation temperature*	Approx. 10.5°C
Glass transition temperature	Approx. 13.3°C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-687 is specifically recommended for the formulation of high performance interior and exterior coatings where excellent adhesion, gloss, durability, water resistance and stain resistance are prerequisites.

TEXICRYL 13-687 exhibits good UV resistance.

PACKAGING AND STORAGE

TEXICRYL 13-687 is supplied in 200 kg lacquer-lined metal drums and minibulk containers. Bulk supplies are delivered by road tanker.

TEXICRYL 13-687 should be stored in the original, unopened and undamaged containers in a dry, well ventilated place at temperatures between 5°C and 30°C. Protect from freezing and direct sunlight.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com



Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com